

PI: Somayeh Nassiri, Associate Professor of UC Davis

# Concrete Construction Recap: Placement, Sampling, and Early Findings

Cells 5, 7, and 9: Construction on September 16, 2025

(CalPortland High-Performance Ternary Blend (IT(L10)(P10)HS) (HPT),  
Fortera reactive calcium carbonate (ReAct), KMI natural pozzolan  
(Zeolite)


October 2025

# Mix Proportions (Batch Size: 6.75 cy)

Item	Units	CEL 5 TR 1-HPT	CEL 5 TR 2-HPT	CEL 7-ReAct	CEL 9-KMI
Batching date-time	-	9/16-6:38 AM	9/16-8:52 AM	9/16-10:57 AM	9/16-1:20 PM
Ambient temperature	°F	58	75	79	90
Test material		Blended cement: Type IT(L10)(P10)HS		Reactive Calcium Carbonate	Zeolite natural pozzolan
Cement	lb/batch (lb/cy)	3982.5 (590)	3,982.5 (590)	1,595 (236)	3180 (472)
Slag (50%)	lb/batch (lb/cy)	-	-	1,994 (295)	-
Other SCM	lb/batch	-	-	399 (10% ReAct)	795 (20% KMI)
Batched Water	gal/batch (gal/cy)	209.9 (31.1)	212.8 (31.5)	209.8 (31.1)	221.4 (32.8)
Added extra water	gal/batch (gal/cy)	32 (4.74)	14 (2.1)	25 (3.7)	20 (3)
Total water	gal/batch (gal/cy)	241.9 (35.84)	226.8 (33.6)	234.8 (34.8)	241.4 (35.7)
Coarse Aggregate	lb/batch	10,600	10,600	10,580	10,580
Int. Aggregate	lb/batch	1,920	1,920	1,920	1,940
Fine Aggregate	lb/batch	8,780	8,800	9,180	8,660
Type A WR, Type B RA, and Type D RA&WR	oz/cwt	4.6	4.8	3	4.8
Initial PCE Type A WR and Type F HRWR	oz/cwt	3	4	3	0
Extra PCE Type A WR and Type F HRWR	oz/cwt	4.5	1.5	6	3
Total PCE Type A WR and Type F HRWR	oz/cwt	7.5	5.5	9	3
Type S SRA	oz/cwt (gal/cy)	32.5 (1.5)	32.5 (1.5)	-	21.7 (1)
Type B RA and Type D RA&WR	oz/cwt	-	-	1	2

RA: retarding admixture  
 WR: water reducer  
 HRWR: high-range water reducer

RA&WR: retarder and water reducer  
 SRA: shrinkage-reducing admixture  
 PCE: Polycarboxylate Ether-based admixture



## CEL 7 (ReAct)



- Batching started at 10:57 AM
- The truck arrived at the site at 11:40 AM
- The ambient temperature at the site was 81°F
- To achieve the desired slump:
  - 25 gal of water and 6 oz/cwt of HRWR were added to the truck
- Initial slump: 5.25in.
- Discharge started at 11:52 AM

# Constructability – CEL 7 (ReAct)



## Constructability – CEL 7 (ReAct)



9/16/2025 11:56 AM

## Constructability – CEL 7 (ReAct)



# Constructability – CEL 7 (ReAct)



9/16/2025 12:00 PM

## Finishability – CEL 7 (ReAct)



- Finishing started at 12:01 PM
- Ambient temp was 82°F
- A small amount of water is being sprayed during placement due to significant slump loss at the end of the placement

# Finishability – CEL 7 (ReAct)



# Finishability – CEL 7 (ReAct)



## Finishability – CEL 7 (ReAct)



9/16/2025 12:16 PM

## Finishability – CEL 7 (ReAct)



## Finishability – CEL 7 (ReAct)



9/16/2025 12:23 PM

## Finishability – CEL 7 (ReAct)



9/16/2025 12:46 PM

## Finishability – CEL 7 (ReAct)



- Slabs covered with wet burlap cover and then sealed with a plastic sheet at 3:30 PM

# Plastic Concrete Test Results

- Slump: ASTM C143, Air Content: ASTM C231, Unit weight: ASTM C138
- Bleed rate: ASTM C232

Property	Unit	CEL 5 TR 1	CEL 5 TR 2	CEL 7	CEL 9
Temperature during slump test	°F	84.2	82.2	87.8	89.6
Initial slump (before discharge)	inch	1.75	None	5.25	8
Final slump (run on sample taken from middle of truck discharge)	inch	6.5	6.25	1	5.5
Air Content	%	Not measured	2	2	1.4
Unit Weight	lb/ft <sup>3</sup>	Not measured	149.1	150.3	148.7
Bleed rate	lb/ft <sup>2</sup> /hr	Not measured	0	0	0

# Plastic Concrete Test Results

Property	Unit	CEL 5 TR 2	CEL 7	CEL 9
Initial Set Time of the sample	h:m (min) since batching time at the plant	4:22 (262)	2:50 (170)	3:17 (197)
Final Set Time of the sample	h:m (min)	5:26 (326)	4:12 (252)	4:21 (261)
Initial Set Maturity	°F-min	13,424	9271	11,798
Final Set Maturity	°F-min	17,273	14,202	17,053
Initial Set Time of the slab	h:m (min)	3:59 (239)	2:47 (167)	3:11 (191)
Final Set Time of the slab	h:m (min)	4:57 (297)	4:01 (241)	4:30 (270)
Start of Saw Cutting Window: =1.3 x final set time at target maturity + 30 min	h:m (since final set time)	7:05	5:52	6:30
Saw Cutting Time	h:m	7:00 AM*	7:20 AM*	7:40 AM*

\*following day

## Why Trial Batching Matters: Moisture & w/c Ratio Verification are Needed

- Allows finalizing the mixing procedure, including water and admixtures
- Verify sand moisture content with the burn method; not relying solely on the sensor
- Observation (supersack discharge method):
  - Higher w/c (furnace-measured) → higher slump and better workability
- Verifying w/c ensures enough water for uniform mixing throughout the load

Cell / Truck	Measured w/c (furnace test)	Calculated w/c (batch records)
Cell 5 (slump=6.5in.)	0.52	0.50
Cell 7 (slump= 3 in.)	0.53	0.51
Cell 9-Truck 1 (dry mi: Slump= 2 in.)	0.50	0.50
Cell 9 -Truck 2 (slump = 5in.)	0.57	0.51

= Lower measured w/c than calculated (low water / poor workability)

= Higher measured w/c than calculated (more water / better workability)



# w/c Verification Results: What They Reveal About Mixing & Workability

Cell / Truck	Measured w/c (furnace test)	Calculated w/c (batch records)	Comments/ Observations
Cell 5 Truck 1 (End-Sample 1)	0.54	0.54	• Lower w/c than calculated → poor mixing / drum residue
Cell 5 Truck 1 (End-Sample 2)	0.53	0.54	
Cell 5 TR 2 (Start)	0.55	0.50	• Higher measured w/c → uniform mixing + water availability
Cell 5 TR 2 (Middle)	0.58	0.50	
Cell 7 (Start)	0.47	0.50	Slump loss tied to lower available water across the batch
Cell 7 (Middle)	0.50	0.50	
Cell 7 (End-Sample 1)	0.55	0.50	
Cell 7 (End-Sample 2)	0.50	0.50	
Cell 9 (Start)	0.55	0.53	• Higher measured w/c → uniform mixing + water availability
Cell 9 (Middle)	0.59	0.53	
Cell 9 (End-Sample 1)	0.55	0.53	
Cell 9 (End-Sample 2)	0.58	0.53	

- = Lower measured w/c than calculated (low water / poor workability)
- = Higher measured w/c than calculated (more water / better workability)


## w/c Ratio Verification Insights-Trial batch day (Sep 15)

Cell / Truck	w/c based on mass loss in furnace at 600 °C	Calculated w/c based on recorded water and admix
HPT-Truck 1 (slump=6.5in.)	0.52	0.50
ReAct Fortera (good-slump= 2.75in.)	0.53	0.51
KMI-Truck 1 (dry mix-Slump= 2 in.)	0.50	0.50
KMI-Truck 2 (good batch=slump = 5in.)	0.57	0.51

- A similar trend is observed in the results of the trial batch day:
  - Mixes with higher measured w/c ratios (determined by the furnace method) produced more workable mixes with higher slump.
- Verifying w/c ratios is important to ensure adequate upfront water and uniform mixing throughout the batch.


# Compressive Strength Test Results

- Compressive strength increased across all mixes from 7 to 28 days, more rapid strength development for KMI.
- By 28 days, all three mixes had a strength of nearly 6,000 psi or greater.




# Flexural Strength Test Results

- All three mixes easily meet the 42-day 650 psi Caltrans requirement and produced exceptionally high flexural strength by 28 days



# Drying Shrinkage Test Results

- KMI mix had 1 gal of SRA per CY, and HPT mix had 1.5 gal of SRA per CY and met Caltrans's 28-day 0.05% requirement
- C-FA (25% coal fly ash) and Purebase had no SRA and showed high drying shrinkage. These mixes need SRA to meet the requirement
- ReAct/slag mix had a slightly higher drying shrinkage than KMI and HPT, but still much lower than C-FA and Purebase. A dose of SRA is required to meet the spec



# What's Next?

- **Share Construction Recap Materials**
  - Post the recap presentation on the Lab2Slab website and email the link to all attendees.
- **Continue Data Analysis**
  - Review and analyze instrumentation data along with other field and laboratory results.
- **Plan the Next Meeting**
  - Schedule a mid-year or annual meeting to discuss findings and next steps.
- **Publish Annual Updates**
  - Post summarized field and lab data on the Lab2Slab website for member access.
- **Present findings** — CalCIMA and ACI Spring Convention.
- **Prepare next test cells** — Planning and design for the upcoming construction are underway.

# Thank you!!

- Reports will be posted at:
- <https://mdsc.ucdavis.edu/lab2slab/>
- <https://ucprc.ucdavis.edu/publications>



[News](#) [Events](#) [Lab2Slab Initiative](#) [Research & Publications](#) [People](#) [Affiliates](#) [Get Involved](#)

## Join Our Mailing List

As an academic research center, we respect your privacy. You will not receive frequent emails from us, and your data will only be used if it pertains to the specific research conducted here.

Name

Email \*

### Learn About Lab2Slab

- ▶ [Lab2Slab Home](#)
- ▶ [Research & Testing](#)
- ▶ [Publications & Data](#)
- ▶ [Projects](#)
- ▶ [People](#)
- ▶ [Industry Engagement](#)
- ▶ [Affiliates](#)